

UPSOL CHAMPION MATIC
MOTORCYCLE OIL
SAE 10W30
API SL
DESCRIPTION

UPSOL CHAMPION MATIC is a high quality four stroke automatic motor oil equipped with quality additives and an anti-friction formula designed to reduce friction at high temperatures and high speeds. Has a low viscosity to facilitate oil circulation, maximize engine acceleration and save fuel. This lubricant is highly recommended for lubricating four stroke motorcycle engines with a dry clutch system.

TYPICAL CHARACTERISTICS		
PROPERTIES	METHOD	UPSOL CHAMPION MATIC
SAE Viscosity Grade		10W-30
Density at 15°C, kg/l	ASTM D - 4052	0.8539
Kinematic Viscosity at 40°C, cSt at 100°C, cSt	ASTM D - 445	70.35
		11.71
Viscosity Index	ASTM D - 2270	162
Colour	Visual	Red
Flash Point, °C	ASTM D - 92	240
Pour Point, °C	ASTM D - 5950	-27
Total Base Number, mg KOH/g	ASTM D - 2896	7

PERFORMANCE LEVELS

UPSOL CHAMPION MATIC has performance level API SL JASO MB

APPLICATIONS

UPSOL CHAMPION MATIC is highly recommended for matic four stroke motor engines such as Honda, Yamaha, Suzuki, Kawasaki, Kanzen. This oil is also suitable for four stroke motor engines made in America, Euro, China, and others.

SUPERIORITIES/BENEFITS

- Maximize engine acceleration.
- Contains anti-friction to make the engine light, smooth and cool.
- Contains special additives to reduce friction at high temperatures and speeds.
- Has SAE 10W-30 viscosity that is suitable for the latest generation of motor engines; quickly start under cold condition, better cooling effect and fuel efficiency.
- Provides excellent protection for engines which operate under high speed condition.
- Keeps engine clean.
- Protects engine from corrosion and keeps engine components from wear.