



Technical Data Sheet

- Reliable Protection
- Industrial Applications

UPSOL CHAMPION 4T

Motorcycle Oil

SAE 10W-40 API SN

UPSOL CHAMPION 4T is a high quality four stroke motorcycle multigrade lubricant formulated from high quality base oil and API SN additives with Japan technology and formulation. This lubricant has passed high yield variable speed tests over high traction reference oils to ensure no wet clutch slippage in its field applications.

TYPICAL CHARACTERISTICS		
PROPERTIES	METHOD	CHAMPION 4T
SAE Viscosity Grade		10W-40
Density at 15°C, kg/l	ASTM D - 4052	0.8741
Kinematic Viscosity at 40°C, cSt	ASTM D - 445	104.9
100°C, cSt		15.69
Viscosity Index	ASTM D - 2270	159
Colour	Visual	Red
Flash Point, °C	ASTM D - 92	224
Pour Point, °C	ASTM D - 5950	-30
Total Base Number, mg KOH/g	ASTM D - 2896	7

APPLICATIONS

UPSOL CHAMPION 4T is recommended for four stroke motor engine such as Honda, Yamaha, Suzuki, Kawasaki. This oil is also suitable for four stroke motor engines made in America, Euro, China, and others.

PERFORMANCE LEVELS

UPSOL CHAMPION 4T meets API SN.

