



Technical Data Sheet

- Reliable Protection
- Industrial Applications

UPSOL CHAMPION MATIC

Motorcycle Oil

SAE 10W-30 API SL / JASO MB

UPSOL CHAMPION MATIC is a high quality four stroke automatic motor oil equipped with high quality additives and formula using Japan technology and formulation designed to reduce scraping at high temperatures and high speeds. Has a low viscosity to facilitate oil circulation, maximize engine acceleration and save fuel. This lubricant is highly recommended for lubricating four stroke motorcycle engines with a dry clutch system.

TYPICAL CHARACTERISTICS		
PROPERTIES	METHOD	CHAMPION MATIC
SAE Viscosity Grade		10W-30
Density at 15°C, kg/l	ASTM D - 4052	0.8539
Kinematic Viscosity at 40°C, cSt	ASTM D - 445	70.35
100°C, cSt		11.71
Viscosity Index	ASTM D - 2270	162
Colour	Visual	Red
Flash Point, °C	ASTM D - 92	240
Pour Point, °C	ASTM D - 5950	-27
Total Base Number, mg KOH/g	ASTM D - 2896	7

APPLICATIONS

UPSOL CHAMPION MATIC is highly recommended for matic four stroke motor engines such as Honda, Yamaha, Suzuki, Kawasaki, Kanzen. This oil is also suitable for four stroke motor engines made in America, Euro, China, and others.

PERFORMANCE LEVELS

UPSOL CHAMPION MATIC has performance level API SL / JASO MB.

