



Technical Data Sheet

- Reliable Protection
- Industrial Applications

UPSOL MAX POWER XT 15W-40

Diesel Engine Oil

SAE 15W-40 API CI-4

UPSOL MAX POWER XT CI-4 is a high quality heavy duty diesel engine oil that has multi grade viscosity and has the highest performance rating, by API Service Category. This lubricant is suitable for heavy duty diesel engines which are widely available in vehicles, heavy equipment, generator sets, ship engines and locomotive engines. Specially formulated for use in the latest heavy duty diesel engines using EGR (Exhaust Gas Recirculation) technology with low levels of NOx and particulate emissions.

TYPICAL CHARACTERISTICS		
PROPERTIES	METHOD	MAX POWER XT
SAE Viscosity Grade		15W-40
Kinematic Viscosity at 40°C, cSt	ASTM D - 445	102.30
100°C, cSt		14.23
Viscosity Index	ASTM D - 2270	142
Flash Point, °C	ASTM D - 92	220
Pour Point, °C	ASTM D - 5950	-30
Total Base Number, mg KOH/g	ASTM D - 2896	10

APPLICATIONS

UPSOL MAX POWER XT is used in heavy duty diesel engines, direct injection type, equipped with turbocharger and using high speed diesel fuel with maximum Sulphur content up to 0.5%. Specially formulated, so it can be used in the latest diesel engine that using EGR (Exhaust Gas Recirculation) technology.

PERFORMANCE LEVELS

UPSOL MAX POWER XT exceeds the performance levels API CI-4.

