



Technical Data Sheet

- Reliable Protection
- Industrial Applications

UPSOL SHOCK ABSORBER OIL

Specialties

UPSOL SHOCK ABSORBER is a shock absorber lubricant that can be used for all types of shock absorbers used in various types of vehicles, both motorcycles and other vehicles. This lubricant is especially designed using high quality base oil and additives, and is formulated using technology that has been adapted to all types of shock absorbers.

TYPICAL CHARACTERISTICS		
PROPERTIES	METHOD	SHOCK ABSORBER
ISO Viscosity Grade		32
Density at 15°C, kg/l	ASTM D - 4052	0.8797
Kinematic Viscosity at 40°C, cSt	ASTM D - 445	33.11
100°C, cSt		5.90
Viscosity Index	ASTM D - 2270	123
Flash Point, °C	ASTM D - 92	213
Pour Point, °C	ASTM D - 5950	-32

APPLICATIONS

UPSOL SHOCK ABSORBER is recommended for all types of motorcycle shock absorbers and other vehicles, and meets the standards of every shock breaker manufacturer.

SUPERIORITIES / BENEFITS

- Stable and constant absorption of lubricant at high speed compression
- Provides better traction, resulting in reduced tire abrasion
- Designed for high compression speeds in off road conditions of high difficulty

