



## Technical Data Sheet

- Reliable Protection
- Industrial Applications

# UPSOL AUTO GEAR 90, 140 GL-5

Automotive Gear Oil

SAE 90, 140 GL-5

UPSOL AUTO GEAR Series high performance heavy duty gear oil is formulated from high quality base oils and selected additive such as Extreme Pressure additive of sulphur phosphorus type which is anglamol.

TYPICAL CHARACTERISTICS			
PROPERTIES	METHOD	SAE 90	SAE 140
SAE Viscosity Grade		90	140
Density at 15°C, kg/l	ASTM D - 4052	0.9001	0.9054
Kinematic Viscosity at 40°C, cSt	ASTM D - 445	183.30	412.32
100°C, cSt		17.02	28.45
Viscosity Index	ASTM D - 2270	98	96
Flash Point, °C	ASTM D - 92	237	249
Pour Point, °C	ASTM D - 5950	-24	-9

## APPLICATIONS

UPSOL AUTO GEAR 90, 140 GL-5 is recommended for lubrication of gear, particularly hypoid gears on final drive of motor vehicle with heavy duty operating condition.

## PERFORMANCE LEVELS

UPSOL AUTO GEAR 90, 140 GL-5 exceeds the performance levels API GL-5.

