



## Technical Data Sheet

- Reliable Protection
- Industrial Applications

# UPSOL SUPER CHASSIS

Heavy Duty Grease

## NLGI 2, 3

UPSOL SUPER CHASSIS Grease are conventional lubricating greases produced from base oil, calcium thickener, rust and oxidation inhibitors and tackiness additives.

TYPICAL CHARACTERISTICS		
PROPERTIES	NLGI 2	NLGI 3
NLGI Grade	2	3
Thickener Type	Calcium	Calcium
Dropping Point, ASTM D 2265, °C	108	108
Worked Penetration, ASTM D 217, mm/10 @25°C	275	226
Water Washout @79°C, ASTM D 1264, wt %	2.0	1.7
Copper Corrosion ASTM D 4048, Rating	1A	1A
Color	Green	Green

## APPLICATIONS

UPSOL SUPER CHASSIS Grease are recommended for use in chassis and suspension system for motor vehicles of farm tractors such as shafts joints, ball joints, coil springs. UPSOL SUPER CHASSIS Grease can be used with normal operating temperature up to 70°C.

## PROPERTIES / BENEFITS

- Provide excellent water resistance
- Protect metal surfaces from rust and corrosion of severe water exposure
- Prevent dust and dirt from reaching into the moving parts

